

tf.compat.v1.metrics.recall Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/metrics/recall

Computes the recall of the predictions with respect to the labels.

Function Signatures

```
tf.compat.v1.metrics.recall( labels, predictions,  
weights=None, metrics_collections=None,  
updates_collections=None, name=None )
```

Code Examples

```
tf.compat.v1.metrics.recall(  
    labels,  
    predictions,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

```
tf.compat.v1.metrics.recall(  
    labels,  
    predictions,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

Documentation

Computes the recall of the predictions with respect to the labels.

Used in the notebooks

- Exploring the TF-Hub CORD-19 Swivel Embeddings

The recall function creates two local variables, `true_positives` and `false_negatives`, that are used to compute the recall. This value is ultimately returned as recall, an idempotent operation that simply divides `true_positives` by the sum of `true_positives` and `false_negatives`.

For estimation of the metric over a stream of data, the function creates an `update_op` that updates these variables and returns the recall. `update_op` weights each prediction by the corresponding value in `weights`.

If `weights` is `None`, `weights` default to 1. Use `weights` of 0 to mask values.

Returns

`## Raises`