

tf.compat.v1.mixed_precision.FixedLossScale

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/mixed_precision/FixedLossScale

Loss scale with a fixed value.

Function Signatures

```
tf.compat.v1.mixed_precision.FixedLossScale( loss_scale_value
)
```

Code Examples

```
tf.compat.v1.mixed_precision.FixedLossScale(  
    loss_scale_value  
)
```

```
tf.compat.v1.mixed_precision.FixedLossScale(  
    loss_scale_value  
)
```

```
@classmethod  
from_config(  
    config  
)
```

```
@classmethod
```

```
from_config(  
    config  
)
```

```
get_config()
```

```
get_config()
```

```
update(  
    grads  
)
```

Documentation

Loss scale with a fixed value.

Inherits From: `LossScale`

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.mixed_precision.experimental.FixedLossScale`,
`tf.compat.v1.train.experimental.FixedLossScale`

The loss scale is not updated for the lifetime of instances of this class.
A given instance of this class always returns the same number when called.

Raises

Methods

from_config

View source

Creates the `LossScale` from its config.

get_config

View source

Returns the config of this loss scale.

update

[View source](#)

Updates the value of the loss scale.

The loss scale will be potentially updated, based on the value of grads. The tensor returned by calling this class is only updated when this function is evaluated.

In eager mode, this directly updates the loss scale, so that calling `__call__` will return the newly updated loss scale. In graph mode, this returns an op that, when evaluated, updates the loss scale.

This function also returns a `should_apply_gradients` bool. If False, gradients should not be applied to the variables that step, as nonfinite gradients were found, and the loss scale has been be updated to reduce the chance of finding nonfinite gradients in the next step. Some loss scale classes will always return True, as they cannot adjust themselves in response to nonfinite gradients.

When a `DistributionStrategy` is used, this function may only be called in a cross-replica context.

`__call__`

[View source](#)

Returns the current loss scale as a scalar float32 tensor.

