

tf.compat.v1.nn.bidirectional_dynamic_rnn

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/nn/bidirectional_dynamic_rnn

*Creates a dynamic version of bidirectional recurrent neural network.
(deprecated)*

Function Signatures

```
tf.compat.v1.nn.bidirectional_dynamic_rnn( cell_fw, cell_bw,
inputs, sequence_length=None, initial_state_fw=None,
initial_state_bw=None, dtype=None, parallel_iterations=None,
swap_memory=False, time_major=False, scope=None )
keras.layers.Bidirectional(keras.layers.RNN(cell))
```

Code Examples

```
tf.compat.v1.nn.bidirectional_dynamic_rnn(  
    cell_fw,  
    cell_bw,  
    inputs,  
    sequence_length=None,  
    initial_state_fw=None,  
    initial_state_bw=None,  
    dtype=None,  
    parallel_iterations=None,  
    swap_memory=False,  
    time_major=False,  
    scope=None  
)
```

```
tf.compat.v1.nn.bidirectional_dynamic_rnn(  
    cell_fw,  
    cell_bw,  
    inputs,  
    sequence_length=None,  
    initial_state_fw=None,  
    initial_state_bw=None,  
    dtype=None,  
    parallel_iterations=None,  
    swap_memory=False,  
    time_major=False,  
    scope=None  
)
```

Documentation

Creates a dynamic version of bidirectional recurrent neural network. (deprecated)

Takes input and builds independent forward and backward RNNs. The `input_size` of forward and backward cell must match. The initial state for both directions is zero by default (but can be set optionally) and no intermediate states are ever returned -- the network is fully unrolled for the given (passed in) `length(s)` of the sequence(s) or completely unrolled if `length(s)` is not given.

Returns

Raises