

tf.compat.v1.nn.conv1d Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/nn/conv1d

*Computes a 1-D convolution of input with rank ≥ 3 and a 3-D filter.
(deprecated argument values) (deprecated argument values)*

Function Signatures

```
tf.compat.v1.nn.conv1d( value=None, filters=None,  
    stride=None, padding=None, use_cudnn_on_gpu=None,  
    data_format=None, name=None, input=None, dilations=None )  
(data_format='NCHW')
```

Code Examples

```
tf.compat.v1.nn.conv1d(  
    value=None,  
    filters=None,  
    stride=None,  
    padding=None,  
    use_cudnn_on_gpu=None,  
    data_format=None,  
    name=None,  
    input=None,  
    dilations=None  
)
```

```
tf.compat.v1.nn.conv1d(  
    value=None,  
    filters=None,  
    stride=None,  
    padding=None,  
    use_cudnn_on_gpu=None,  
    data_format=None,  
    name=None,  
    input=None,  
    dilations=None  
)
```

Documentation

Computes a 1-D convolution of input with rank ≥ 3 and a 3-D filter. (deprecated argument values) (deprecated argument values)

Given an input tensor of shape

`batch_shape + [in_width, in_channels]`

if `data_format` is "NWC", or

`batch_shape + [in_channels, in_width]`

if `data_format` is "NCW",

and a filter / kernel tensor of shape

`[filter_width, in_channels, out_channels]`, this op reshapes

the arguments to pass them to `conv2d` to perform the equivalent convolution operation.

Internally, this op reshapes the input tensors and invokes `tf.nn.conv2d`.

For example, if `data_format` does not start with "NC", a tensor of shape

`batch_shape + [in_width, in_channels]`

is reshaped to

`batch_shape + [1, in_width, in_channels]`,

and the filter is reshaped to

`[1, filter_width, in_channels, out_channels]`.

The result is then reshaped back to

`batch_shape + [out_width, out_channels]`

(where `out_width` is a function of the stride and padding as in `conv2d`) and returned to the caller.

Returns

Raises

