

tf.compat.v1.nn.nce_loss Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/nn/nce_loss

Computes and returns the noise-contrastive estimation training loss.

Function Signatures

```
tf.compat.v1.nn.nce_loss( weights, biases, labels, inputs,  
num_sampled, num_classes, num_true=1, sampled_values=None,  
remove_accidental_hits=False, partition_strategy='mod',  
name='nce_loss' )
```

Code Examples

```
tf.compat.v1.nn.nce_loss(  
weights,  
biases,  
labels,  
inputs,  
num_sampled,  
num_classes,  
num_true=1,  
sampled_values=None,  
remove_accidental_hits=False,  
partition_strategy='mod',  
name='nce_loss'  
)
```

```
tf.compat.v1.nn.nce_loss(  
weights,  
biases,  
labels,  
inputs,  
num_sampled,  
num_classes,  
num_true=1,  
sampled_values=None,  
remove_accidental_hits=False,  
partition_strategy='mod',  
name='nce_loss'  
)
```

```
if mode == "train":
    loss = tf.nn.nce_loss(
        weights=weights,
        biases=biases,
        labels=labels,
        inputs=inputs,
        ...,
        partition_strategy="div")
elif mode == "eval":
    logits = tf.matmul(inputs, tf.transpose(weights))
    logits = tf.nn.bias_add(logits, biases)
    labels_one_hot = tf.one_hot(labels, n_classes)
    loss = tf.nn.sigmoid_cross_entropy_with_logits(
        labels=labels_one_hot,
        logits=logits)
    loss = tf.reduce_sum(loss, axis=1)
```

```
if mode == "train":
    loss = tf.nn.nce_loss(
        weights=weights,
        biases=biases,
        labels=labels,
        inputs=inputs,
        ...,
        partition_strategy="div")
elif mode == "eval":
    logits = tf.matmul(inputs, tf.transpose(weights))
    logits = tf.nn.bias_add(logits, biases)
    labels_one_hot = tf.one_hot(labels, n_classes)
    loss = tf.nn.sigmoid_cross_entropy_with_logits(
        labels=labels_one_hot,
        logits=logits)
    loss = tf.reduce_sum(loss, axis=1)
```

Documentation

Computes and returns the noise-contrastive estimation training loss.

A common use case is to use this method for training, and calculate the full sigmoid loss for evaluation or inference. In this case, you must set `partition_strategy="div"` for the two losses to be consistent, as in the following example:

Returns

References