

tf.compat.v1.nn.relu6 Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/nn/relu6

Computes Rectified Linear 6: $\min(\max(\text{features}, 0), 6)$.

Function Signatures

```
min(max(features, 0), 6)
tf.compat.v1.nn.relu6( features, name=None )
x = tf.constant([-3.0, -1.0, 0.0, 6.0, 10.0],
dtype=tf.float32)
y = tf.nn.relu6(x)
```

Code Examples

```
tf.compat.v1.nn.relu6(  
    features, name=None  
)
```

```
tf.compat.v1.nn.relu6(  
    features, name=None  
)
```

```
x = tf.constant([-3.0, -1.0, 0.0, 6.0, 10.0], dtype=tf.float32)  
y = tf.nn.relu6(x)  
y.numpy()  
array([0., 0., 0., 6., 6.], dtype=float32)
```

```
x = tf.constant([-3.0, -1.0, 0.0, 6.0, 10.0], dtype=tf.float32)
```

```
y = tf.nn.relu6(x)
```

```
array([0., 0., 0., 6., 6.], dtype=float32)
```

Documentation

Computes Rectified Linear 6: $\min(\max(\text{features}, 0), 6)$.

In comparison with `tf.nn.relu`, `relu6` activation functions have shown to empirically perform better under low-precision conditions (e.g. fixed point inference) by encouraging the model to learn sparse features earlier.

Source: Convolutional Deep Belief Networks on CIFAR-10: Krizhevsky et al., 2010.

For example:

Returns

References