

tf.compat.v1.nn.sparse_softmax_cross_entropy_with_logits

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/nn/sparse_softmax_cross_entropy_with_logits

Computes sparse softmax cross entropy between logits and labels.

Function Signatures

```
tf.compat.v1.nn.sparse_softmax_cross_entropy_with_logits(  
    labels=None, logits=None, name=None )
```

Code Examples

```
tf.compat.v1.nn.sparse_softmax_cross_entropy_with_logits(  
    labels=None, logits=None, name=None  
)
```

```
tf.compat.v1.nn.sparse_softmax_cross_entropy_with_logits(  
    labels=None, logits=None, name=None  
)
```

Documentation

Computes sparse softmax cross entropy between logits and labels.

Used in the notebooks

- Migrate metrics and optimizers
- Exploring the TF-Hub CORD-19 Swivel Embeddings

Measures the probability error in discrete classification tasks in which the classes are mutually exclusive (each entry is in exactly one class). For example, each CIFAR-10 image is labeled with one and only one label: an image can be a dog or a truck, but not both.

A common use case is to have logits of shape `[batch_size, num_classes]` and have labels of shape `[batch_size]`, but higher dimensions are supported, in which case the dim-th dimension is assumed to be of size `num_classes`. logits must have the dtype of `float16`, `float32`, or `float64`, and labels must have the dtype of `int32` or `int64`.

Note that to avoid confusion, it is required to pass only named arguments to this function.

Returns

Raises

