

tf.compat.v1.nn.static_bidirectional_rnn

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/nn/static_bidirectional_rnn

Creates a bidirectional recurrent neural network. (deprecated)

Function Signatures

```
tf.compat.v1.nn.static_bidirectional_rnn( cell_fw, cell_bw,
inputs, initial_state_fw=None, initial_state_bw=None,
dtype=None, sequence_length=None, scope=None )
keras.layers.Bidirectional(keras.layers.RNN(cell,
unroll=True))
```

Code Examples

```
tf.compat.v1.nn.static_bidirectional_rnn(  
    cell_fw,  
    cell_bw,  
    inputs,  
    initial_state_fw=None,  
    initial_state_bw=None,  
    dtype=None,  
    sequence_length=None,  
    scope=None  
)
```

```
tf.compat.v1.nn.static_bidirectional_rnn(  
    cell_fw,  
    cell_bw,  
    inputs,  
    initial_state_fw=None,  
    initial_state_bw=None,  
    dtype=None,  
    sequence_length=None,  
    scope=None  
)
```

Documentation

Creates a bidirectional recurrent neural network. (deprecated)

Similar to the unidirectional case above (rnn) but takes input and builds independent forward and backward RNNs with the final forward and backward outputs depth-concatenated, such that the output will have the format [time][batch][cell_fw.output_size + cell_bw.output_size]. The input_size of forward and backward cell must match. The initial state for both directions is zero by default (but can be set optionally) and no intermediate states are ever returned -- the network is fully unrolled for the given (passed in) length(s) of the sequence(s) or completely unrolled if length(s) is not given.

Returns

Raises