

tf.compat.v1.ones_initializer Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/ones_initializer

Initializer that generates tensors initialized to 1.

Function Signatures

```
tf.compat.v1.ones_initializer( dtype=tf.dtypes.float32 )
```

Code Examples

```
tf.compat.v1.ones_initializer(  
dtype=tf.dtypes.float32  
)
```

```
tf.compat.v1.ones_initializer(  
dtype=tf.dtypes.float32  
)
```

```
tf.dtypes.float32
```

```
>>> initializer = tf.compat.v1.keras.initializers.ones()  
>>> initializer((1, 1))
```

```
>>> initializer = tf.compat.v1.keras.initializers.ones()  
>>> initializer((1, 1))
```

```
>>> initializer = tf.keras.initializers.ones()  
>>> initializer((1, 1))
```

```
>>> initializer = tf.keras.initializers.ones()  
>>> initializer((1, 1))
```

```
@classmethod  
from_config(  
config  
)
```

Documentation

Initializer that generates tensors initialized to 1.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.initializers.ones`

Migrate to TF2

This API is compatible with TF2 behavior and `tf.function`, and can be migrated immediately with `tf.keras.initializers.ones`.

Before:

After:

Description

Used in the notebooks

- Use TF1.x models in TF2 workflows

Methods

from_config

[View source](#)

Instantiates an initializer from a configuration dictionary.

Example:

```
## get_config
```

[View source](#)

Returns the configuration of the initializer as a JSON-serializable dict.

`__call__`

[View source](#)

Returns a tensor object initialized as specified by the initializer.