

tf.compat.v1.ragged.constant_value Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/ragged/constant_value

Constructs a RaggedTensorValue from a nested Python list.

Function Signatures

```
tf.compat.v1.ragged.constant_value( pylist, dtype=None,  
ragged_rank=None, inner_shape=None, row_splits_dtype='int64'  
) -> Union[tf.compat.v1.ragged.RaggedTensorValue, np.ndarray]
```

Code Examples

```
tf.compat.v1.ragged.constant_value(  
pylist,  
dtype=None,  
ragged_rank=None,  
inner_shape=None,  
row_splits_dtype='int64'  
) -> Union[tf.compat.v1.ragged.RaggedTensorValue, np.ndarray]
```

```
tf.compat.v1.ragged.constant_value(  
    pylist,  
    dtype=None,  
    ragged_rank=None,  
    inner_shape=None,  
    row_splits_dtype='int64'  
) -> Union[tf.compat.v1.ragged.RaggedTensorValue, np.ndarray]
```

```
tf.compat.v1.ragged.RaggedTensorValue
```

```
tf.compat.v1.ragged.constant_value([[1, 2], [3], [4, 5, 6]])  
tf.RaggedTensorValue(values=array([1, 2, 3, 4, 5, 6]),  
    row_splits=array([0, 2, 3, 6]))
```

```
tf.compat.v1.ragged.constant_value([[1, 2], [3], [4, 5, 6]])
```

```
tf.RaggedTensorValue(values=array([1, 2, 3, 4, 5, 6]),
```

```
    row_splits=array([0, 2, 3, 6]))
```

Documentation

Constructs a `RaggedTensorValue` from a nested Python list.

Example:

All scalar values in `pylist` must have the same nesting depth `K`, and the returned `RaggedTensorValue` will have rank `K`. If `pylist` contains no scalar values, then `K` is one greater than the maximum depth of empty lists in `pylist`. All scalar values in `pylist` must be compatible with `dtype`.

- `1 - len(inner_shape)` if `inner_shape` is specified.

`inner_shape`

A tuple of integers specifying the shape for individual inner values in the returned `RaggedTensorValue`. Defaults to `()` if `ragged_rank` is not specified. If `ragged_rank` is specified, then a default is chosen based on the contents of `pylist`. `row_splits_dtype` data type for the constructed `RaggedTensorValue`'s `row_splits`. One of `numpy.int32` or `numpy.int64`.

Returns

Raises