

# tf.compat.v1.reduce\_any Stay organized with collections Save and categorize content based on your preferences.

[https://www.tensorflow.org/api\\_docs/python/tf/compat/v1/reduce\\_any](https://www.tensorflow.org/api_docs/python/tf/compat/v1/reduce_any)

---

*Computes `tf.math.logical_or` of elements across dimensions of a tensor.  
(deprecated arguments)*

## Function Signatures

---

```
tf.compat.v1.reduce_any( input_tensor, axis=None,  
keepdims=None, name=None, reduction_indices=None,  
keep_dims=None )  
(keep_dims)
```

## Code Examples

---

```
tf.compat.v1.reduce_any(  
    input_tensor,  
    axis=None,  
    keepdims=None,  
    name=None,  
    reduction_indices=None,  
    keep_dims=None  
)
```

```
tf.compat.v1.reduce_any(  
    input_tensor,  
    axis=None,  
    keepdims=None,  
    name=None,  
    reduction_indices=None,  
    keep_dims=None  
)
```

```
>>> x = tf.constant([[True,  True], [False, False]])  
>>> tf.reduce_any(x)  
  
>>> tf.reduce_any(x, 0)  
  
>>> tf.reduce_any(x, 1)
```

```
>>> x = tf.constant([[True,  True], [False, False]])  
>>> tf.reduce_any(x)  
  
>>> tf.reduce_any(x, 0)  
  
>>> tf.reduce_any(x, 1)
```

# Documentation

---

Computes `tf.math.logical_or` of elements across dimensions of a tensor.  
(deprecated arguments)

## View aliases

Compat aliases for migration

See

Migration guide for  
more details.

`tf.compat.v1.math.reduce_any`

This is the reduction operation for the elementwise `tf.math.logical_or` op.

Reduces `input_tensor` along the dimensions given in `axis`.

Unless `keepdims` is true, the rank of the tensor is reduced by 1 for each of the entries in `axis`, which must be unique. If `keepdims` is true, the reduced dimensions are retained with length 1.

If `axis` is `None`, all dimensions are reduced, and a tensor with a single element is returned.

## For example

## Returns

## numpy compatibility

Equivalent to `np.any`

