

tf.compat.v1.scatter_mul Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/scatter_mul

Multiplies sparse updates into a variable reference.

Function Signatures

```
tf.compat.v1.scatter_mul( ref, indices, updates,
use_locking=False, name=None )

# Scalar indices ref[indices, ...] *= updates[...] # Vector
indices (for each i) ref[indices[i], ...] *= updates[i, ...]
# High rank indices (for each i, ..., j) ref[indices[i, ...,
j], ...] *= updates[i, ..., j, ...]
```

Code Examples

```
tf.compat.v1.scatter_mul(  
    ref, indices, updates, use_locking=False, name=None  
)
```

```
tf.compat.v1.scatter_mul(  
    ref, indices, updates, use_locking=False, name=None  
)
```

```
# Scalar indices  
ref[indices, ...] *= updates[...]  
# Vector indices (for each i)  
ref[indices[i], ...] *= updates[i, ...]  
# High rank indices (for each i, ..., j)  
ref[indices[i, ..., j], ...] *= updates[i, ..., j, ...]
```

```
# Scalar indices  
ref[indices, ...] *= updates[...]  
# Vector indices (for each i)  
ref[indices[i], ...] *= updates[i, ...]  
# High rank indices (for each i, ..., j)  
ref[indices[i, ..., j], ...] *= updates[i, ..., j, ...]
```

Documentation

Multiplies sparse updates into a variable reference.

This operation computes

This operation outputs ref after the update is done.

This makes it easier to chain operations that need to use the reset value.

Duplicate entries are handled correctly: if multiple indices reference the same location, their contributions multiply.

Requires `updates.shape = indices.shape + ref.shape[1:]` or `updates.shape = []`.

Returns