

tf.compat.v1.string_split Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/string_split

Split elements of source based on delimiter. (deprecated arguments)

Function Signatures

```
tf.compat.v1.string_split( source, sep=None, skip_empty=True,  
delimiter=None, result_type='SparseTensor', name=None )  
(delimiter)
```

Code Examples

```
tf.compat.v1.string_split(  
source,  
sep=None,  
skip_empty=True,  
delimiter=None,  
result_type='SparseTensor',  
name=None  
)
```

```
tf.compat.v1.string_split(  
    source,  
    sep=None,  
    skip_empty=True,  
    delimiter=None,  
    result_type='SparseTensor',  
    name=None  
)
```

```
print(tf.compat.v1.string_split(['hello world', 'a b c']))  
SparseTensor(indices=tf.Tensor( [[0 0] [0 1] [1 0] [1 1] [1 2]],  
    ...),  
    values=tf.Tensor([b'hello' b'world' b'a' b'b' b'c'], ...),  
    dense_shape=tf.Tensor([2 3], shape=(2,), dtype=int64))
```

```
print(tf.compat.v1.string_split(['hello world', 'a b c']))
```

```
SparseTensor(indices=tf.Tensor( [[0 0] [0 1] [1 0] [1 1] [1 2]],  
    ...),
```

```
values=tf.Tensor([b'hello' b'world' b'a' b'b' b'c'], ...),
```

```
dense_shape=tf.Tensor([2 3], shape=(2,), dtype=int64))
```

```
print(tf.compat.v1.string_split(['hello world', 'a b c'],  
    result_type="RaggedTensor"))
```

Documentation

Split elements of source based on delimiter. (deprecated arguments)

Let N be the size of source (typically N will be the batch size). Split each element of source based on delimiter and return a SparseTensor or RaggedTensor containing the split tokens. Empty tokens are ignored.

If sep is an empty string, each element of the source is split into individual strings, each containing one byte. (This includes splitting multibyte sequences of UTF-8.) If delimiter contains multiple bytes, it is treated as a set of delimiters with each considered a potential split point.

Examples:

Raises

Returns