

tf.compat.v1.tables_initializer Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/tables_initializer

Returns an Op that initializes all tables of the default graph.

Function Signatures

```
tf.compat.v1.tables_initializer( name='init_all_tables' )
```

Code Examples

```
tf.compat.v1.tables_initializer(  
    name='init_all_tables'  
)
```

```
tf.compat.v1.tables_initializer(  
    name='init_all_tables'  
)
```

```
with tf.compat.v1.Session():
    init = tf.compat.v1.lookup.KeyValueTensorInitializer(['a', 'b'],
    [1, 2])
    table = tf.compat.v1.lookup.StaticHashTable(init, default_value=-1)
    tf.compat.v1.tables_initializer().run()
    result = table.lookup(tf.constant(['a', 'c'])).eval()
    result
    array([ 1, -1], dtype=int32)
```

```
with tf.compat.v1.Session():
```

```
    init = tf.compat.v1.lookup.KeyValueTensorInitializer(['a', 'b'],
    [1, 2])
```

```
    table = tf.compat.v1.lookup.StaticHashTable(init, default_value=-1)
```

```
    tf.compat.v1.tables_initializer().run()
```

```
    result = table.lookup(tf.constant(['a', 'c'])).eval()
```

Documentation

Returns an Op that initializes all tables of the default graph.

View aliases

Compat aliases for migration

See

Migration guide for

more details.

`tf.compat.v1.initializers.tables_initializer`

Migrate to TF2

`tf.compat.v1.tables_initializer` is no longer needed with eager execution and `tf.function`. In TF2, when creating an initializable table like a `tf.lookup.StaticHashTable`, the table will automatically be initialized on creation.

Before & After Usage Example

Before:

After:

Description

Used in the notebooks

- Universal Sentence Encoder-Lite demo
- Wiki40B Language Models

Returns