

tf.compat.v1.variables_initializer Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/variables_initializer

Returns an Op that initializes a list of variables.

Function Signatures

```
tf.compat.v1.variables_initializer( var_list, name='init' )  
initialize_variables()
```

Code Examples

```
tf.compat.v1.variables_initializer(  
var_list, name='init'  
)
```

```
tf.compat.v1.variables_initializer(  
var_list, name='init'  
)
```

Documentation

Returns an Op that initializes a list of variables.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.initializers.variables`

Migrate to TF2

In TF2, variables are initialized immediately when they are created. There is no longer a need to run variable initializers before using them.

Description

Used in the notebooks

- Tutorial on Multi Armed Bandits in TF-Agents

After you launch the graph in a session, you can run the returned Op to initialize all the variables in `var_list`. This Op runs all the initializers of the variables in `var_list` in parallel.

Calling `initialize_variables()` is equivalent to passing the list of initializers to `Group()`.

If `var_list` is empty, however, the function still returns an Op that can be run. That Op just has no effect.

Returns

Generated on 10/25/2025 | TensorFlow Documentation Scraper