

tf.conv Stay organized with collections

Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/conv

Computes a N-D convolution given $(N+1+batch_dims)$ -D input and $(N+2)$ -D filter tensors.

Function Signatures

```
tf.conv( input: Annotated[Any, TV_Conv_T], filter:
Annotated[Any, TV_Conv_T], strides, padding: str,
explicit_paddings=[], data_format: str = 'CHANNELS_LAST',
dilations=[], batch_dims: int = 1, groups: int = 1, name=None
) -> Annotated[Any, TV_Conv_T]
```

Code Examples

```
tf.conv(
input: Annotated[Any, TV_Conv_T],
filter: Annotated[Any, TV_Conv_T],
strides,
padding: str,
explicit_paddings=[],
data_format: str = 'CHANNELS_LAST',
dilations=[],
batch_dims: int = 1,
groups: int = 1,
name=None
) -> Annotated[Any, TV_Conv_T]
```

```
tf.conv(
input: Annotated[Any, TV_Conv_T],
filter: Annotated[Any, TV_Conv_T],
strides,
padding: str,
explicit_paddings=[],
data_format: str = 'CHANNELS_LAST',
dilations=[],
batch_dims: int = 1,
groups: int = 1,
name=None
) -> Annotated[Any, TV_Conv_T]
```

Documentation

Computes a N-D convolution given (N+1+batch_dims)-D input and (N+2)-D filter tensors.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.conv`

General function for computing a N-D convolution. It is required that $1 \leq N \leq 3$.

Returns