

tf.get_current_name_scope Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/get_current_name_scope

Returns current full name scope specified by `tf.name_scope(...)`s.

Function Signatures

```
tf.name_scope(...)
tf.get_current_name_scope() -> str
with tf.name_scope("outer"): tf.get_current_name_scope() #
"outer" with tf.name_scope("inner"):
tf.get_current_name_scope() # "outer/inner"
tf.get_current_name_scope()
```

Code Examples

```
tf.get_current_name_scope() -> str
```

```
tf.get_current_name_scope() -> str
```

```
with tf.name_scope("outer"):
    tf.get_current_name_scope() # "outer"
    with tf.name_scope("inner"):
        tf.get_current_name_scope() # "outer/inner"
```

```
with tf.name_scope("outer"):
    tf.get_current_name_scope() # "outer"
    with tf.name_scope("inner"):
        tf.get_current_name_scope() # "outer/inner"
```

```
with tf.name_scope("outer"):
    @tf.function
    def foo(x):
        with tf.name_scope("inner"):
            return tf.add(x * x) # Op name is "inner/Add", not
                                "outer/inner/Add"
```

```
with tf.name_scope("outer"):
    @tf.function
    def foo(x):
        with tf.name_scope("inner"):
            return tf.add(x * x) # Op name is "inner/Add", not
                                "outer/inner/Add"
```

Documentation

Returns current full name scope specified by `tf.name_scope(...)`s.

For example,

In other words, `tf.get_current_name_scope()` returns the op name prefix that will be prepended to, if an op is created at that place.

Note that `@tf.function` resets the name scope stack as shown below.