

tf.ifftnd Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/ifftnd

ND inverse fast Fourier transform.

Function Signatures

```
tf.ifftnd( input: Annotated[Any, TV_IFFTND_Tcomplex],  
fft_length: Annotated[Any, _atypes.Int32], axes:  
Annotated[Any, _atypes.Int32], name=None ) -> Annotated[Any,  
TV_IFFTND_Tcomplex]
```

Code Examples

```
tf.ifftnd(  
input: Annotated[Any, TV_IFFTND_Tcomplex],  
fft_length: Annotated[Any, _atypes.Int32],  
axes: Annotated[Any, _atypes.Int32],  
name=None  
) -> Annotated[Any, TV_IFFTND_Tcomplex]
```

```
tf.ifftnd(  
input: Annotated[Any, TV_IFFTND_Tcomplex],  
fft_length: Annotated[Any, _atypes.Int32],  
axes: Annotated[Any, _atypes.Int32],  
name=None  
) -> Annotated[Any, TV_IFFTND_Tcomplex]
```

Documentation

ND inverse fast Fourier transform.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.ifftnd`

Computes the n-dimensional inverse discrete Fourier transform over designated dimensions of input. The designated dimensions of input are assumed to be the result of IFFTND.

If `fft_length[i] > shape(input)[i]`, the input is padded with zeros. If `fft_length` is not given, the default `shape(input)` is used.

Axes mean the dimensions to perform the transform on. Default is to perform on all axes.

Returns