

tf.print Stay organized with collections

Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/print

Print the specified inputs.

Function Signatures

```
tf.print( *inputs, **kwargs )
tensor = tf.range(10) tf.print(tensor,
output_stream=sys.stderr)
tensor = tf.range(10) tf.print("tensors:", tensor, {2: tensor
* 2}, output_stream=sys.stdout)
tensor_a = tf.range(2) tensor_b = tensor_a * 2
tf.print(tensor_a, tensor_b, output_stream=sys.stderr,
sep=',')
```

Code Examples

```
tf.print(
*inputs, **kwargs
)
```

```
tf.print(  
    *inputs, **kwargs  
)
```

```
tensor = tf.range(10)  
tf.print(tensor, output_stream=sys.stderr)
```

```
tensor = tf.range(10)  
tf.print(tensor, output_stream=sys.stderr)
```

```
tensor = tf.range(10)  
tf.print("tensors:", tensor, {2: tensor * 2},  
output_stream=sys.stdout)
```

```
tensor = tf.range(10)  
tf.print("tensors:", tensor, {2: tensor * 2},  
output_stream=sys.stdout)
```

```
tensor_a = tf.range(2)  
tensor_b = tensor_a * 2  
tf.print(tensor_a, tensor_b, output_stream=sys.stderr, sep=',')
```

```
tensor_a = tf.range(2)  
tensor_b = tensor_a * 2  
tf.print(tensor_a, tensor_b, output_stream=sys.stderr, sep=',')
```

Documentation

Print the specified inputs.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.print`

Used in the notebooks

- Better performance with `tf.function`
 - Better performance with the `tf.data` API
 - Debug a TensorFlow 2 migrated training pipeline
 - Distributed Input

A TensorFlow operator that prints the specified inputs to a desired output stream or logging level. The inputs may be dense or sparse Tensors, primitive python objects, data structures that contain tensors, and printable Python objects. Printed tensors will recursively show the first and last elements of each dimension to summarize.

Example

(This prints "[0 1 2 ... 7 8 9]" to `sys.stderr`)

Multi-input usage:

(This prints "tensors: [0 1 2 ... 7 8 9] {2: [0 2 4 ... 14 16 18]}" to `sys.stdout`)

Changing the input separator:

(This prints "[0 1],[0 2]" to sys.stderr)

Usage in a tf.function:

(This prints "[0 1 2 ... 7 8 9]" to sys.stderr)

Compatibility usage in TF 1.x graphs:

In graphs manually created outside of tf.function, this method returns the created TF operator that prints the data. To make sure the operator runs, users need to pass the produced op to tf.compat.v1.Session's run method, or to use the op as a control dependency for executed ops by specifying with tf.compat.v1.control_dependencies([print_op]).

(This prints "tensors: [0 1 2 ... 7 8 9] {2: [0 2 4 ... 14 16 18]}" to sys.stdout)

Returns

Raises