

# tf.random\_normal\_initializer Stay organized with collections Save and categorize content based on your preferences.

[https://www.tensorflow.org/api\\_docs/python/tf/random\\_normal\\_initializer](https://www.tensorflow.org/api_docs/python/tf/random_normal_initializer)

---

*Initializer that generates tensors with a normal distribution.*

## Function Signatures

---

```
tf.random_normal_initializer( mean=0.0, stddev=0.05,
seed=None )
def make_variables(k, initializer):
return (tf.Variable(initializer(shape=[k],
dtype=tf.float32)),
tf.Variable(initializer(shape=[k, k], dtype=tf.float32)))
```

## Code Examples

---

```
tf.random_normal_initializer(
mean=0.0, stddev=0.05, seed=None
)
```

```
tf.random_normal_initializer(  
mean=0.0, stddev=0.05, seed=None  
)
```

```
def make_variables(k, initializer):  
    return (tf.Variable(initializer(shape=[k], dtype=tf.float32)),  
            tf.Variable(initializer(shape=[k, k], dtype=tf.float32)))  
    v1, v2 = make_variables(3,  
        tf.random_normal_initializer(mean=1., stddev=2.))  
    v1  
  
    v2  
    ,
```

```
def make_variables(k, initializer):
```

```
    return (tf.Variable(initializer(shape=[k], dtype=tf.float32)),
```

```
            tf.Variable(initializer(shape=[k, k], dtype=tf.float32)))
```

```
    v1, v2 = make_variables(3,
```

```
tf.random_normal_initializer(mean=1., stddev=2.))
```

# Documentation

---

Initializer that generates tensors with a normal distribution.

## Used in the notebooks

- pix2pix: Image-to-image translation with a conditional GAN

Initializers allow you to pre-specify an initialization strategy, encoded in the Initializer object, without knowing the shape and dtype of the variable being initialized.

## Examples:

## Methods

### from\_config

[View source](#)

Instantiates an initializer from a configuration dictionary.

## Example:

## get\_config

[View source](#)

Returns the configuration of the initializer as a JSON-serializable dict.

### \_\_call\_\_

[View source](#)

Returns a tensor object initialized as specified by the initializer.

