

tf.rfftnd Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/rfftnd

ND fast real Fourier transform.

Function Signatures

```
tf.rfftnd( input: Annotated[Any, TV_RFFTND_Treal],  
fft_length: Annotated[Any, _atypes.Int32], axes:  
Annotated[Any, _atypes.Int32], Tcomplex: TV_RFFTND_Tcomplex =  
tf.dtypes.complex64, name=None ) -> Annotated[Any,  
TV_RFFTND_Tcomplex]
```

Code Examples

```
tf.rfftnd(  
input: Annotated[Any, TV_RFFTND_Treal],  
fft_length: Annotated[Any, _atypes.Int32],  
axes: Annotated[Any, _atypes.Int32],  
Tcomplex: TV_RFFTND_Tcomplex = tf.dtypes.complex64,  
name=None  
) -> Annotated[Any, TV_RFFTND_Tcomplex]
```

```
tf.rfftnd(  
input: Annotated[Any, TV_RFFTND_Treal],  
fft_length: Annotated[Any, _atypes.Int32],  
axes: Annotated[Any, _atypes.Int32],  
Tcomplex: TV_RFFTND_Tcomplex = tf.dtypes.complex64,  
name=None  
) -> Annotated[Any, TV_RFFTND_Tcomplex]
```

```
tf.dtypes.complex64
```

Documentation

ND fast real Fourier transform.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.rfftnd`

Computes the n-dimensional real discrete Fourier transform over designated dimensions of input. The designated dimensions of input are assumed to be the result of RFFTND. The length of the last axis transformed will be `fft_length[-1]//2+1`.

If `fft_length[i] > shape(input)[i]`, the input is padded with zeros. If `fft_length` is not given, the default `shape(input)` is used.

Axes mean the dimensions to perform the transform on. Default is to perform on all axes.

Returns