

tf.stack Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/stack

Stacks a list of rank- R tensors into one rank- $(R+1)$ tensor.

Function Signatures

$(R+1)$
`tf.stack( values, axis=0, name='stack' )`

Code Examples

```
tf.stack(  
values, axis=0, name='stack'  
)
```

```
tf.stack(  
values, axis=0, name='stack'  
)
```

```
x = tf.constant([1, 4])
y = tf.constant([2, 5])
z = tf.constant([3, 6])
tf.stack([x, y, z])

tf.stack([x, y, z], axis=1)
```

```
x = tf.constant([1, 4])
```

```
y = tf.constant([2, 5])
```

```
z = tf.constant([3, 6])
```

```
tf.stack([x, y, z])
```

Documentation

Stacks a list of rank- R tensors into one rank- $(R+1)$ tensor.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.stack`

Used in the notebooks

- Extension types
 - `tf.data`: Build TensorFlow input pipelines
 - TensorFlow basics
 - Random number generation
 - Time series forecasting
 - Custom training: walkthrough
 - `pix2pix`: Image-to-image translation with a conditional GAN
 - Overfit and underfit
 - Load CSV data

See also `tf.concat`, `tf.tile`, `tf.repeat`.

Packs the list of tensors in values into a tensor with rank one higher than each tensor in values, by packing them along the axis dimension.

Given a list of length `N` of tensors of shape `(A, B, C)`;

if `axis == 0` then the output tensor will have the shape `(N, A, B, C)`.

if `axis == 1` then the output tensor will have the shape `(A, N, B, C)`.

Etc.

For example:

This is the opposite of `unstack`. The numpy equivalent is `np.stack`

Returns

Raises

Generated on 10/25/2025 | TensorFlow Documentation Scraper