

tf.tensor_scatter_nd_max Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/tensor_scatter_nd_max

Apply a sparse update to a tensor taking the element-wise maximum.

Function Signatures

```
tf.tensor_scatter_nd_max( tensor: Annotated[Any,  
TV_TensorScatterMax_T], indices: Annotated[Any,  
TV_TensorScatterMax_Tindices], updates: Annotated[Any,  
TV_TensorScatterMax_T], name=None ) -> Annotated[Any,  
TV_TensorScatterMax_T]
```

Code Examples

```
tf.tensor_scatter_nd_max(  
    tensor: Annotated[Any, TV_TensorScatterMax_T],  
    indices: Annotated[Any, TV_TensorScatterMax_Tindices],  
    updates: Annotated[Any, TV_TensorScatterMax_T],  
    name=None  
) -> Annotated[Any, TV_TensorScatterMax_T]
```

```
tf.tensor_scatter_nd_max(  
  tensor: Annotated[Any, TV_TensorScatterMax_T],  
  indices: Annotated[Any, TV_TensorScatterMax_Tindices],  
  updates: Annotated[Any, TV_TensorScatterMax_T],  
  name=None  
) -> Annotated[Any, TV_TensorScatterMax_T]
```

```
tensor = [0, 0, 0, 0, 0, 0, 0, 0]  
indices = [[1], [4], [5]]  
updates = [1, -1, 1]  
tf.tensor_scatter_nd_max(tensor, indices, updates).numpy()  
array([0, 1, 0, 0, 0, 1, 0, 0], dtype=int32)
```

```
tensor = [0, 0, 0, 0, 0, 0, 0, 0]
```

```
indices = [[1], [4], [5]]
```

```
updates = [1, -1, 1]
```

```
tf.tensor_scatter_nd_max(tensor, indices, updates).numpy()
```

```
array([0, 1, 0, 0, 0, 1, 0, 0], dtype=int32)
```

Documentation

Apply a sparse update to a tensor taking the element-wise maximum.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.tensor_scatter_nd_max`

Used in the notebooks

- Introduction to tensor slicing

Returns a new tensor copied from tensor whose values are element-wise maximum between
tensor and updates according to the indices.

Refer to `tf.tensor_scatter_nd_update` for more details.

Returns