

tf.type_spec_from_value Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/type_spec_from_value

Returns a tf.TypeSpec that represents the given value.

Function Signatures

```
tf.type_spec_from_value( value ) -> tf.TypeSpec
```

Code Examples

```
tf.type_spec_from_value(  
    value  
) -> tf.TypeSpec
```

```
tf.type_spec_from_value(  
    value  
) -> tf.TypeSpec
```

```
tf.TypeSpec
```

```
>>> tf.type_spec_from_value(tf.constant([1, 2, 3]))
TensorSpec(shape=(3,), dtype=tf.int32, name=None)
>>> tf.type_spec_from_value(np.array([4.0, 5.0], np.float64))
TensorSpec(shape=(2,), dtype=tf.float64, name=None)
>>> tf.type_spec_from_value(tf.ragged.constant([[1, 2], [3, 4,
5]]))
RaggedTensorSpec(TensorShape([2, None]), tf.int32, 1, tf.int64)
```

```
>>> tf.type_spec_from_value(tf.constant([1, 2, 3]))
TensorSpec(shape=(3,), dtype=tf.int32, name=None)
>>> tf.type_spec_from_value(np.array([4.0, 5.0], np.float64))
TensorSpec(shape=(2,), dtype=tf.float64, name=None)
>>> tf.type_spec_from_value(tf.ragged.constant([[1, 2], [3, 4,
5]]))
RaggedTensorSpec(TensorShape([2, None]), tf.int32, 1, tf.int64)
```

```
example_input = tf.ragged.constant([[1, 2], [3]])
@tf.function(input_signature=
[tf.type_spec_from_value(example_input)])
def f(x):
return tf.reduce_sum(x, axis=1)
```

```
example_input = tf.ragged.constant([[1, 2], [3]])
```

```
@tf.function(input_signature=
[tf.type_spec_from_value(example_input)])
```

Documentation

Returns a `tf.TypeSpec` that represents the given value.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.type_spec_from_value`

Used in the notebooks

- Extension types

Examples

`## Returns`

`## Raises`