

set_grad_enabled#

https://pytorch.org/docs/stable/generated/torch.autograd.grad_mode.set_grad_enabled.html

Description:

Context-manager that sets gradient calculation on or off. `set_grad_enabled` will enable or disable grads based on its argument `mode`. It can be used as a context-manager or as a function. This context manager is thread local; it will not affect computation in other threads.

`mode (bool)` – Flag whether to enable grad (`True`), or disable (`False`). This can be used to conditionally enable gradients.

Function Signature

```
class torch.autograd.grad_mode.set_grad_enabled(mode)  
[source]#
```

Parameters

Example::

```
clone()[source]#
```

Return type

Returns:

set_grad_enabled

Code Examples

```
>>> x = torch.tensor([1.], requires_grad=True)
>>> is_train = False
>>> with torch.set_grad_enabled(is_train):
...     y = x * 2
>>> y.requires_grad
False
>>> _ = torch.set_grad_enabled(True)
>>> y = x * 2
>>> y.requires_grad
True
>>> _ = torch.set_grad_enabled(False)
>>> y = x * 2
>>> y.requires_grad
False
```

Notes & Warnings

NOTE

Note `set_grad_enabled` is one of several mechanisms that can enable or disable gradients locally see [Locally disabling gradient computation](#) for more information on how they compare.

NOTE

Note This API does not apply to forward-mode AD.

Detailed Documentation

Documentation

Context-manager that sets gradient calculation on or off.

`set_grad_enabled` will enable or disable grads based on its argument mode. It can be used as a context-manager or as a function.

This context manager is thread local; it will not affect computation in other threads.

mode (bool) – Flag whether to enable grad (True), or disable (False). This can be used to conditionally enable gradients.

`set_grad_enabled` is one of several mechanisms that can enable or disable gradients locally see [Locally disabling gradient computation](#) for more information on how they compare.

This API does not apply to forward-mode AD.

Create a copy of this class