

torch.autograd.graph.increment_version

https://pytorch.org/docs/stable/generated/torch.autograd.graph.increment_version.html

Description:

Update autograd metadata tracking whether the given Tensor was modified in place. This is to enable more accurate error checking within the autograd engine. It is already done automatically by PyTorch functions and within custom Function when `mark_dirty()` is called appropriately so you only need to call this explicitly if you are doing inplace operation on the Tensor data in a way that Pytorch doesn't know about. For example a custom kernel that reads the Tensor `data_ptr` and modifies the memory inplace based on this pointer. Can accept either a tensor, or a list of tensors. Note that incrementing the version counter multiple times for a single inplace operation is not problematic. Note that if you pass in tensor constructed under `torch.inference_mode()`, we will not bump its version counter (because your tensor does not have one).

Function Signature

```
torch.autograd.graph.increment_version(tensor)[source]#
```

Detailed Documentation

Documentation

Update autograd metadata tracking whether the given Tensor was modified in place.

This is to enable more accurate error checking within the autograd engine. It is already done automatically by PyTorch functions and within custom Function when `mark_dirty()` is called appropriately so you only need to call this explicitly if you are doing inplace operation on the Tensor data in a way that Pytorch doesn't know about. For example a custom kernel that reads the Tensor `data_ptr` and modifies the memory inplace based on this pointer. Can accept either a tensor, or a list of tensors.

Note that incrementing the version counter multiple times for a single inplace operation is not problematic.

Note that if you pass in tensor constructed under `torch.inference_mode()`, we will not bump its version counter (because your tensor does not have one).