

record_function#

https://pytorch.org/docs/stable/generated/torch.autograd.profiler.record_function.html

Description:

Context manager/function decorator that adds a label to a code block/function when running autograd profiler. Label will only appear if CPU activity tracing is enabled. It is useful when tracing the code profile.

name (str) – Label assigned to the block of code. node_id (int) – ID of node, for distributed profiling. Unset in cases. (non-distributed) –

Function Signature

```
class torch.autograd.profiler.record_function(name,  
args=None)[source]#
```

Parameters

Code Examples

```

>>> x = torch.randn((1, 1), requires_grad=True)
>>> with torch.autograd.profiler.profile() as prof:
...     y = x**2
...     with torch.autograd.profiler.record_function(
...         "label-z"
...     ): # label the block
...         z = y**3
...         y.backward()
>>> # NOTE: some columns were removed for brevity
>>>
print(prof.key_averages().table(sort_by="self_cpu_time_total"))
-----
-----
Name                               Self CPU total %  CPU time
avg      Number of Calls
-----
-----
pow                               60.77%         47.470us
3
mul                               21.73%         25.465us
2
PowBackward0                      12.03%        121.891us
1
torch::autograd::AccumulateGrad    2.70%          6.324us
1
label-z                           2.13%         12.421us
1
torch::autograd::GraphRoot         0.64%          1.503us
1
-----
-----
Self CPU time total: 234.344us
CUDA time total: 0.000us

```

Detailed Documentation

Documentation

Context manager/function decorator that adds a label to a code block/function when running autograd profiler. Label will only appear if CPU activity tracing is enabled.

It is useful when tracing the code profile.

name (str) – Label assigned to the block of code.

node_id (int) – ID of node, for distributed profiling. Unset in

cases. (non-distributed) –

Context manager/function decorator that adds a label to a code block/function when running autograd profiler. Label will only appear if CPU activity tracing is enabled.

It is useful when tracing the code profile.

name (str) – Label assigned to the block of code.

name (str) – Label assigned to the block of code.

node_id (int) – ID of node, for distributed profiling. Unset in

node_id (int) – ID of node, for distributed profiling. Unset in

cases. (non-distributed) –

cases. (non-distributed) –

