

StringTable#

https://pytorch.org/docs/stable/generated/torch.autograd.profiler_util.StringTable.html

Description:

Factory for default value called by `__missing__()`. Create a new dictionary with keys from iterable and values set to value. Return the value for key if key is in the dictionary, else default. If the key is not found, return the default if given; otherwise, raise a `KeyError`. Remove and return a (key, value) pair as a 2-tuple.

Function Signature

```
class torch.autograd.profiler_util.StringTable[source]#  
clear() → None. Remove all items from D.#  
copy() → a shallow copy of D.#  
default_factory#  
fromkeys(value=None, /)#
```

Detailed Documentation

Documentation

Factory for default value called by `__missing__()`.

Create a new dictionary with keys from iterable and values set to value.

Return the value for key if key is in the dictionary, else default.

If the key is not found, return the default if given; otherwise, raise a `KeyError`.

Remove and return a (key, value) pair as a 2-tuple.

Pairs are returned in LIFO (last-in, first-out) order. Raises `KeyError` if the dict is empty.

Insert key with a value of default if key is not in the dictionary.

Return the value for key if key is in the dictionary, else default.

If E is present and has a `.keys()` method, then does: for k in E: $D[k] = E[k]$ If E is present and lacks a `.keys()` method, then does: for k, v in E: $D[k] = v$ In either case, this is followed by: for k in F: $D[k] = F[k]$