

torch.jit.script_if_tracing#

https://pytorch.org/docs/stable/generated/torch.jit.script_if_tracing.html#t

Description:

Compiles `fn` when it is first called during tracing. `torch.jit.script` has a non-negligible start up time when it is first called due to lazy-initializations of many compiler builtins. Therefore you should not use it in library code. However, you may want to have parts of your library work in tracing even if they use control flow. In these cases, you should use `@torch.jit.script_if_tracing` to substitute for `torch.jit.script`. `fn` – A function to compile. If called during tracing, a `ScriptFunction` created by `torch.jit.script` is returned. Otherwise, the original function `fn` is returned.

Function Signature

```
torch.jit.script_if_tracing(fn)[source]#
```

Parameters

Returns

Returns:

If called during tracing, a `ScriptFunction` created by `torch.jit.script` is returned. Otherwise, the original function `fn` is returned.

Detailed Documentation

Documentation

Compiles `fn` when it is first called during tracing.

`torch.jit.script` has a non-negligible start up time when it is first called due to lazy-initializations of many compiler builtins. Therefore you should not use it in library code. However, you may want to have parts of your library work in tracing even if they use control flow. In these cases, you should use `@torch.jit.script_if_tracing` to substitute for `torch.jit.script`.

`fn` – A function to compile.

If called during tracing, a `ScriptFunction` created by `torch.jit.script` is returned. Otherwise, the original function `fn` is returned.