

# Hardsigmoid#

<https://pytorch.org/docs/stable/generated/torch.nn.Hardsigmoid.html>

## Description:

Applies the Hardsigmoid function element-wise. Hardsigmoid is defined as: inplace (bool) – can optionally do the operation in-place. Default: False Input:  $(*)^{(*)}(*)$ , where  $*^{**}$  means any number of dimensions. Output:  $(*)^{(*)}(*)$ , same shape as the input.

## Function Signature

---

```
class torch.nn.Hardsigmoid(inplace=False)[source]#
```

Parameters

Shape:

```
forward(input)[source]#
```

Return type

## Returns:

Tensor

## Code Examples

---

```
>>> m = nn.Hardsigmoid()  
>>> input = torch.randn(2)  
>>> output = m(input)
```

# Detailed Documentation

---

## Documentation

Applies the Hardsigmoid function element-wise.

Hardsigmoid is defined as:

inplace (bool) – can optionally do the operation in-place. Default: False

Input:  $(*)^{(*)} (*)$ , where  $*^{**}$  means any number of dimensions.

Output:  $(*)^{(*)} (*)$ , same shape as the input.

Runs the forward pass.

Applies the Hardsigmoid function element-wise.

Hardsigmoid is defined as:

inplace (bool) – can optionally do the operation in-place. Default: False

Input:  $(*)^{(*)} (*)$ , where  $*^{**}$  means any number of dimensions.

Input:  $(*)^{(*)} (*)$ , where  $*^{**}$  means any number of dimensions.

Output:  $(*)^{(*)} (*)$ , same shape as the input.

Output:  $(*)^{(*)} (*)$ , same shape as the input.

Runs the forward pass.

