

Hardsigmoid#

<https://pytorch.org/docs/stable/generated/torch.nn.Hardsigmoid.html#torch.nn>

Description:

Applies the Hardsigmoid function element-wise. Hardsigmoid is defined as: inplace (bool) – can optionally do the operation in-place. Default: False Input: $(*)^{(*)}(*)$, where $*^{**}$ means any number of dimensions. Output: $(*)^{(*)}(*)$, same shape as the input.

Function Signature

```
class torch.nn.Hardsigmoid(inplace=False)[source]#
```

Parameters

Shape:

```
forward(input)[source]#
```

Return type

Returns:

Tensor

Code Examples

```
>>> m = nn.Hardsigmoid()  
>>> input = torch.randn(2)  
>>> output = m(input)
```

Detailed Documentation

Documentation

Applies the Hardsigmoid function element-wise.

Hardsigmoid is defined as:

inplace (bool) – can optionally do the operation in-place. Default: False

Input: $(*)^{(*)} (*)$, where $*^{**}$ means any number of dimensions.

Output: $(*)^{(*)} (*)$, same shape as the input.

Runs the forward pass.

Applies the Hardsigmoid function element-wise.

Hardsigmoid is defined as:

inplace (bool) – can optionally do the operation in-place. Default: False

Input: $(*)^{(*)} (*)$, where $*^{**}$ means any number of dimensions.

Input: $(*)^{(*)} (*)$, where $*^{**}$ means any number of dimensions.

Output: $(*)^{(*)} (*)$, same shape as the input.

Output: $(*)^{(*)} (*)$, same shape as the input.

Runs the forward pass.

