

Hardswish#

<https://pytorch.org/docs/stable/generated/torch.nn.Hardswish.html#torch.nn.H>

Description:

Applies the Hardswish function, element-wise. Method described in the paper: Searching for MobileNetV3. Hardswish is defined as: inplace (bool) – can optionally do the operation in-place. Default: False Input: $(*)$ $(*)(*)$, where $***$ means any number of dimensions.

Function Signature

```
class torch.nn.Hardswish(inplace=False)[source]#
```

Parameters

Shape:

```
forward(input)[source]#
```

Return type

Returns:

Tensor

Code Examples

```
>>> m = nn.Hardswish()  
>>> input = torch.randn(2)  
>>> output = m(input)
```

Detailed Documentation

Documentation

Applies the Hardswish function, element-wise.

Method described in the paper: Searching for MobileNetV3.

Hardswish is defined as:

`inplace (bool)` – can optionally do the operation in-place. Default: False

Input: $(*)^{(*)}(*)$, where $*^{**}$ means any number of dimensions.

Output: $(*)^{(*)}(*)$, same shape as the input.

Runs the forward pass.

Applies the Hardswish function, element-wise.

Method described in the paper: Searching for MobileNetV3.

Hardswish is defined as:

inplace (bool) – can optionally do the operation in-place. Default: False

Input: $(*)^{(*)} (*)$, where $*^{**}$ means any number of dimensions.

Input: $(*)^{(*)} (*)$, where $*^{**}$ means any number of dimensions.

Output: $(*)^{(*)} (*)$, same shape as the input.

Output: $(*)^{(*)} (*)$, same shape as the input.

Runs the forward pass.