

# Hardtanh#

<https://pytorch.org/docs/stable/generated/torch.nn.Hardtanh.html>

## Description:

Applies the HardTanh function element-wise. HardTanh is defined as:

min\_val (float) – minimum value of the linear region range. Default: -1

max\_val (float) – maximum value of the linear region range. Default: 1

inplace (bool) – can optionally do the operation in-place. Default: False

## Function Signature

---

```
class torch.nn.Hardtanh(min_val=-1.0, max_val=1.0,  
inplace=False, min_value=None, max_value=None)[source]#
```

Parameters

Shape:

```
extra_repr()[source]#
```

Return type

**Returns:**

Tensor

## Code Examples

---

```
>>> m = nn.Hardtanh(-2, 2)
>>> input = torch.randn(2)
>>> output = m(input)
```

# Detailed Documentation

---

## Documentation

Applies the HardTanh function element-wise.

HardTanh is defined as:

`min_val` (float) – minimum value of the linear region range. Default: -1

`max_val` (float) – maximum value of the linear region range. Default: 1

`inplace` (bool) – can optionally do the operation in-place. Default: False

Keyword arguments `min_value` and `max_value` have been deprecated in favor of `min_val` and `max_val`.

Input:  $(*)^{(*)} (*)$ , where  $***$  means any number of dimensions.

Output:  $(*)^{(*)} (*)$ , same shape as the input.

Return the extra representation of the module.

Runs the forward pass.