

# LeakyReLU#

<https://pytorch.org/docs/stable/generated/torch.nn.LeakyReLU.html>

## Description:

Applies the LeakyReLU function element-wise. `negative_slope` (float) – Controls the angle of the negative slope (which is used for negative input values). Default: 1e-2 `inplace` (bool) – can optionally do the operation in-place. Default: False Input:  $(*)^{(*)} (*)$  where  $*$  means, any number of additional dimensions

## Function Signature

---

```
class torch.nn.LeakyReLU(negative_slope=0.01, inplace=False)  
[source]#
```

Parameters

Shape:

```
extra_repr()[source]#
```

Return type

## Returns:

Tensor

## Code Examples

---

```
>>> m = nn.LeakyReLU(0.1)
>>> input = torch.randn(2)
>>> output = m(input)
```

## Detailed Documentation

---

### Documentation

Applies the LeakyReLU function element-wise.

`negative_slope` (float) – Controls the angle of the negative slope (which is used for negative input values). Default: 1e-2

`inplace` (bool) – can optionally do the operation in-place. Default: False

Input:  $(*) (*) (*)$  where  $*$  means, any number of additional dimensions

Output:  $(*) (*) (*)$ , same shape as the input

Return the extra representation of the module.

Applies the LeakyReLU function element-wise.

`negative_slope` (float) – Controls the angle of the negative slope (which is used for negative input values). Default: 1e-2

`negative_slope` (float) – Controls the angle of the negative slope (which is used for negative input values). Default: 1e-2

`inplace` (bool) – can optionally do the operation in-place. Default: False

`inplace` (bool) – can optionally do the operation in-place. Default: False

Input:  $(*)^{(*)} (*)$  where  $*$  means, any number of additional dimensions

Input:  $(*)^{(*)} (*)$  where  $*$  means, any number of additional dimensions

Output:  $(*)^{(*)} (*)$ , same shape as the input

Output:  $(*)^{(*)} (*)$ , same shape as the input

Return the extra representation of the module.