

LeakyReLU#

<https://pytorch.org/docs/stable/generated/torch.nn.LeakyReLU.html#torch.nn.L>

Description:

Applies the LeakyReLU function element-wise. `negative_slope` (float) – Controls the angle of the negative slope (which is used for negative input values). Default: 1e-2 `inplace` (bool) – can optionally do the operation in-place. Default: False Input: $(*)^{(*)} (*)$ where $*$ means, any number of additional dimensions

Function Signature

```
class torch.nn.LeakyReLU(negative_slope=0.01, inplace=False)  
[source]#
```

Parameters

Shape:

```
extra_repr()[source]#
```

Return type

Returns:

Tensor

Code Examples

```
>>> m = nn.LeakyReLU(0.1)
>>> input = torch.randn(2)
>>> output = m(input)
```

Detailed Documentation

Documentation

Applies the LeakyReLU function element-wise.

`negative_slope` (float) – Controls the angle of the negative slope (which is used for negative input values). Default: 1e-2

`inplace` (bool) – can optionally do the operation in-place. Default: False

Input: $(*) (*) (*)$ where $*$ means, any number of additional dimensions

Output: $(*) (*) (*)$, same shape as the input

Return the extra representation of the module.

Applies the LeakyReLU function element-wise.

`negative_slope` (float) – Controls the angle of the negative slope (which is used for negative input values). Default: 1e-2

`negative_slope` (float) – Controls the angle of the negative slope (which is used for negative input values). Default: 1e-2

`inplace` (bool) – can optionally do the operation in-place. Default: False

`inplace` (bool) – can optionally do the operation in-place. Default: False

Input: $(*)^{(*)} (*)$ where $*$ means, any number of additional dimensions

Input: $(*)^{(*)} (*)$ where $*$ means, any number of additional dimensions

Output: $(*)^{(*)} (*)$, same shape as the input

Output: $(*)^{(*)} (*)$, same shape as the input

Return the extra representation of the module.