

MaxPool3d#

<https://pytorch.org/docs/stable/generated/torch.nn.MaxPool3d.html>

Description:

Applies a 3D max pooling over an input signal composed of several input planes. In the simplest case, the output value of the layer with input size (N, C, D, H, W) , output $(N, C, D_{out}, H_{out}, W_{out})$ and kernel_size (kD, kH, kW) can be precisely described as: If padding is non-zero, then the input is implicitly padded with negative infinity on both sides for padding number of points. dilation controls the spacing between the kernel points. It is harder to describe, but this link has a nice visualization of what dilation does. When `ceil_mode=True`, sliding windows are allowed to go off-bounds if they start within the left padding or the input. Sliding windows that would start in the right padded region are ignored.

Function Signature

```
class torch.nn.MaxPool3d(kernel_size, stride=None,
padding=0, dilation=1, return_indices=False,
ceil_mode=False)[source]#
```

Parameters

Shape:

```
forward(input)[source]#
```

Code Examples

```
>>> # pool of square window of size=3, stride=2
>>> m = nn.MaxPool3d(3, stride=2)
>>> # pool of non-square window
>>> m = nn.MaxPool3d((3, 2, 2), stride=(2, 1, 2))
>>> input = torch.randn(20, 16, 50, 44, 31)
>>> output = m(input)
```

Notes & Warnings

NOTE When `ceil_mode=True`, sliding windows are allowed to go off-bounds if they start within the left padding or the input. Sliding windows that would start in the right padded region are ignored.

Detailed Documentation

Documentation

Applies a 3D max pooling over an input signal composed of several input planes.

In the simplest case, the output value of the layer with input size (N, C, D, H, W) (N, C, D, H, W) , output $(N, C, D_{out}, H_{out}, W_{out})$ $(N, C, D_{out}, H_{out}, W_{out})$ and kernel_size (kD, kH, kW) (kD, kH, kW) can be precisely described as:

If padding is non-zero, then the input is implicitly padded with negative infinity on both sides for padding number of points. dilation controls the spacing between the kernel points. It is harder to describe, but this link has a nice visualization of what dilation does.

When ceil_mode=True, sliding windows are allowed to go off-bounds if they start within the left padding or the input. Sliding windows that would start in the right padded region are ignored.

The parameters kernel_size, stride, padding, dilation can either be:

a single int – in which case the same value is used for the depth, height and width dimension

a tuple of three ints – in which case, the first int is used for the depth dimension, the second int for the height dimension and the third int for the width dimension

kernel_size (Union[int, tuple[int, int, int]]) – the size of the window to take a max over

stride (Union[int, tuple[int, int, int]]) – the stride of the window. Default value is

`kernel_size`

`padding` (`Union[int, tuple[int, int, int]]`) – Implicit negative infinity padding to be added on all three sides

`dilation` (`Union[int, tuple[int, int, int]]`) – a parameter that controls the stride of elements in the window

`return_indices` (`bool`) – if `True`, will return the max indices along with the outputs. Useful for `torch.nn.MaxUnpool3d` later

`ceil_mode` (`bool`) – when `True`, will use `ceil` instead of `floor` to compute the output shape

Input: $(N, C, D_{in}, H_{in}, W_{in})$ or $(N, C, D_{in}, H_{in}, W_{in})$ or $(C, D_{in}, H_{in}, W_{in})$ or $(C, D_{in}, H_{in}, W_{in})$

Output: $(N, C, D_{out}, H_{out}, W_{out})$ or $(N, C, D_{out}, H_{out}, W_{out})$ or $(C, D_{out}, H_{out}, W_{out})$ or $(C, D_{out}, H_{out}, W_{out})$, where

Runs the forward pass.