

ReLU6#

<https://pytorch.org/docs/stable/generated/torch.nn.ReLU6.html>

Description:

Applies the ReLU6 function element-wise. inplace (bool) – can optionally do the operation in-place. Default: False Input: $(*)^{(*)}(*)$, where $*^{**}$ means any number of dimensions. Output: $(*)^{(*)}(*)$, same shape as the input.

Function Signature

```
class torch.nn.ReLU6(inplace=False)[source]#
```

Parameters

Shape:

```
extra_repr()[source]#
```

Return type

Returns:

str

Code Examples

```
>>> m = nn.ReLU6()  
>>> input = torch.randn(2)  
>>> output = m(input)
```

Detailed Documentation

Documentation

Applies the ReLU6 function element-wise.

`inplace` (bool) – can optionally do the operation in-place. Default: False

Input: $(*)^{(*)} (*)$, where $***$ means any number of dimensions.

Output: $(*)^{(*)} (*)$, same shape as the input.

Return the extra representation of the module.

Applies the ReLU6 function element-wise.

`inplace` (bool) – can optionally do the operation in-place. Default: False

Input: $(*)^{(*)} (*)$, where $***$ means any number of dimensions.

Input: $(*)^{(*)} (*)$, where $***$ means any number of dimensions.

Output: $(*)^{(*)} (*)$, same shape as the input.

Output: $(*)^{(*)} (*)$, same shape as the input.

Return the extra representation of the module.