

UpsamplingNearest2d#

<https://pytorch.org/docs/stable/generated/torch.nn.UpsamplingNearest2d.html#>

Description:

Applies a 2D nearest neighbor upsampling to an input signal composed of several input channels. To specify the scale, it takes either the size or the scale_factor as it's constructor argument. When size is given, it is the output size of the image (h, w). size (int or Tuple[int, int], optional) – output spatial sizes scale_factor (float or Tuple[float, float], optional) – multiplier for spatial size.

Function Signature

```
class torch.nn.UpsamplingNearest2d(size=None,  
scale_factor=None)[source]#
```

Parameters

Shape:

Code Examples

```
>>> input = torch.arange(1, 5, dtype=torch.float32).view(1, 1, 2, 2)
>>> input
tensor([[[[1., 2.],
          [3., 4.]]]])

>>> m = nn.UpsamplingNearest2d(scale_factor=2)
>>> m(input)
tensor([[[[1., 1., 2., 2.],
          [1., 1., 2., 2.],
          [3., 3., 4., 4.],
          [3., 3., 4., 4.]]]])
```

Notes & Warnings

WARNING

Warning This class is deprecated in favor of `interpolate()`.

Detailed Documentation

Documentation

Applies a 2D nearest neighbor upsampling to an input signal composed of several input channels.

To specify the scale, it takes either the size or the `scale_factor` as it's constructor argument.

When size is given, it is the output size of the image (h, w).

size (int or Tuple[int, int], optional) – output spatial sizes

scale_factor (float or Tuple[float, float], optional) – multiplier for spatial size.

This class is deprecated in favor of `interpolate()`.

Input: (N,C,Hin,Win)(N, C, H_{in}, W_{in})(N,C,Hin,Win)

Output: (N,C,Hout,Wout)(N, C, H_{out}, W_{out})(N,C,Hout,Wout) where