

torch.nn.functional.gaussian_nll_loss#

https://pytorch.org/docs/stable/generated/torch.nn.functional.gaussian_nll_loss.html

Description:

Compute the Gaussian negative log likelihood loss. See GaussianNLLLoss for details. input (Tensor) – Expectation of the Gaussian distribution. target (Tensor) – Sample from the Gaussian distribution. var (Union[Tensor, float]) – Tensor of positive variance(s), one for each of the expectations in the input (heteroscedastic), or a single one (homoscedastic), or a positive scalar value to be used for all expectations.

Function Signature

```
torch.nn.functional.gaussian_nll_loss(input, target, var,
full=False, eps=1e-06, reduction='mean')[source]#
```

Parameters

Return type

Returns:

Tensor

Detailed Documentation

Documentation

Compute the Gaussian negative log likelihood loss.

See `GaussianNLLLoss` for details.

`input` (Tensor) – Expectation of the Gaussian distribution.

`target` (Tensor) – Sample from the Gaussian distribution.

`var` (Union[Tensor, float]) – Tensor of positive variance(s), one for each of the expectations in the input (heteroscedastic), or a single one (homoscedastic), or a positive scalar value to be used for all expectations.

`full` (bool, optional) – Whether to include the constant term in the loss calculation. Default: False.

`eps` (float, optional) – Value added to var, for stability. Default: 1e-6.

`reduction` (str, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the output is the average of all batch member losses, 'sum': the output is the sum of all batch member losses. Default: 'mean'.

