

torch.nn.functional.huber_loss#

https://pytorch.org/docs/stable/generated/torch.nn.functional.huber_loss.html

Description:

Compute the Huber loss, with optional weighting. Function uses a squared term if the absolute element-wise error falls below delta and a delta-scaled L1 term otherwise. When delta equals 1, this loss is equivalent to SmoothL1Loss. In general, Huber loss differs from SmoothL1Loss by a factor of delta (AKA beta in Smooth L1). See HuberLoss for details. input (Tensor) – Predicted values.

Function Signature

```
torch.nn.functional.huber_loss(input, target,  
reduction='mean', delta=1.0, weight=None)[source]#
```

Parameters

Returns

Return type

Returns:

Tensor

Detailed Documentation

Documentation

Compute the Huber loss, with optional weighting.

Function uses a squared term if the absolute element-wise error falls below delta and a delta-scaled L1 term otherwise.

When delta equals 1, this loss is equivalent to SmoothL1Loss. In general, Huber loss differs from SmoothL1Loss by a factor of delta (AKA beta in Smooth L1).

See HuberLoss for details.

input (Tensor) – Predicted values.

target (Tensor) – Ground truth values.

reduction (str, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'mean': the mean of the output is taken. 'sum': the output will be summed. 'none': no reduction will be applied. Default: 'mean'.

delta (float, optional) – The threshold at which to change between delta-scaled L1 and L2 loss. Default: 1.0.

weight (Tensor, optional) – Weights for each sample. Default: None.

Huber loss (optionally weighted).

