

torch.nn.functional.pdist#

<https://pytorch.org/docs/stable/generated/torch.nn.functional.pdist.html>

Description:

Computes the p-norm distance between every pair of row vectors in the input. This is identical to the upper triangular portion, excluding the diagonal, of `torch.norm(input[:, None] - input, dim=2, p=p)`. This function will be faster if the rows are contiguous. If input has shape $N \times M$ then the output will have shape $\frac{N(N-1)}{2}$. This function is equivalent to `scipy.spatial.distance.pdist(input, 'minkowski', p=p)` if $p \in (0, \infty)$. When $p=0$ it is equivalent to `scipy.spatial.distance.pdist(input, 'hamming') * M`. When $p=\infty$, the closest scipy function is `scipy.spatial.distance.pdist(xn, lambda x, y: np.abs(x - y).max())`. input – input tensor of shape $N \times M$. p – p value for the p-norm distance to calculate between each vector pair $\in [0, \infty]$.

Function Signature

```
torch.nn.functional.pdist(input, p=2) → Tensor#
```

Parameters

Detailed Documentation

Documentation

Computes the p-norm distance between every pair of row vectors in the input. This is identical to the upper triangular portion, excluding the diagonal, of `torch.norm(input[:, None] - input, dim=2, p=p)`. This function will be faster if the rows are contiguous.

If input has shape $N \times M$ then the output will have shape $\frac{N(N-1)}{2}$.

This function is equivalent to `scipy.spatial.distance.pdist(input, 'minkowski', p=p)` if $p \in (0, \infty)$. When $p=0$ it is equivalent to `scipy.spatial.distance.pdist(input, 'hamming') * M`. When $p=\infty$, the closest scipy function is `scipy.spatial.distance.pdist(xn, lambda x, y: np.abs(x - y).max())`.

input – input tensor of shape $N \times M$.

p – p value for the p-norm distance to calculate between each vector pair $\in [0, \infty]$.

