

torch.nn.functional.pixel_unshuffle#

https://pytorch.org/docs/stable/generated/torch.nn.functional.pixel_unshuffle.html

Description:

Reverses the PixelShuffle operation by rearranging elements in a tensor of shape $(*, C, H \times r, W \times r)$ to a tensor of shape $(*, C \times r^2, H, W)$, where r is the downscale_factor. See PixelUnshuffle for details. input (Tensor) – the input tensor downscale_factor (int) – factor to increase spatial resolution by

Function Signature

```
torch.nn.functional.pixel_unshuffle(input, downscale_factor)
→ Tensor#
```

Parameters

Code Examples

```
>>> input = torch.randn(1, 1, 12, 12)
>>> output = torch.nn.functional.pixel_unshuffle(input, 3)
>>> print(output.size())
torch.Size([1, 9, 4, 4])
```

Detailed Documentation

Documentation

Reverses the PixelShuffle operation by rearranging elements in a tensor of shape $(*, C, H \times r, W \times r)$ to a tensor of shape $(*, C \times r^2, H, W)$, where r is the `downscale_factor`.

See `PixelUnshuffle` for details.

`input (Tensor)` – the input tensor

`downscale_factor (int)` – factor to increase spatial resolution by

Reverses the PixelShuffle operation by rearranging elements in a tensor of shape $(*, C, H \times r, W \times r)$ to a tensor of shape $(*, C \times r^2, H, W)$, where r is the `downscale_factor`.

See `PixelUnshuffle` for details.

`input (Tensor)` – the input tensor

`input (Tensor)` – the input tensor

`downscale_factor (int)` – factor to increase spatial resolution by

`downscale_factor (int)` – factor to increase spatial resolution by