

torch.nn.functional.upsample_bilinear#

https://pytorch.org/docs/stable/generated/torch.nn.functional.upsample_bilinear.html

Description:

Upsamples the input, using bilinear upsampling. This function is deprecated in favor of `torch.nn.functional.interpolate()`. This is equivalent with `nn.functional.interpolate(..., mode='bilinear', align_corners=True)`. Expected inputs are spatial (4 dimensional). Use `upsample_trilinear` for volumetric (5 dimensional) inputs. input (Tensor) – input

Function Signature

```
torch.nn.functional.upsample_bilinear(input, size=None,
scale_factor=None)[source]#
```

Parameters

Notes & Warnings

WARNING

This function is deprecated in favor of `torch.nn.functional.interpolate()`. This is equivalent with `nn.functional.interpolate(..., mode='bilinear', align_corners=True)`.

NOTE

This operation may produce nondeterministic gradients when given tensors on a CUDA device. See [Reproducibility](#) for more information.

Detailed Documentation

Documentation

Upsamples the input, using bilinear upsampling.

This function is deprecated in favor of `torch.nn.functional.interpolate()`. This is equivalent with `nn.functional.interpolate(..., mode='bilinear', align_corners=True)`.

Expected inputs are spatial (4 dimensional). Use `upsample_trilinear` for volumetric (5 dimensional) inputs.

`input (Tensor)` – input

`size (int or Tuple[int, int])` – output spatial size.

`scale_factor (int or Tuple[int, int])` – multiplier for spatial size

This operation may produce nondeterministic gradients when given tensors on a CUDA device. See [Reproducibility](#) for more information.