

UninitializedBuffer#

<https://pytorch.org/docs/stable/generated/torch.nn.parameter.UninitializedBuffer.html>

Description:

A buffer that is not initialized. Uninitialized Buffer is a special case of `torch.Tensor` where the shape of the data is still unknown. Unlike a `torch.Tensor`, uninitialized parameters hold no data and attempting to access some properties, like their shape, will throw a runtime error. The only operations that can be performed on a uninitialized parameter are changing its datatype, moving it to a different device and converting it to a regular `torch.Tensor`. The default device or dtype to use when the buffer is materialized can be set during construction using e.g. `device='cuda'`.

Function Signature

```
class
torch.nn.parameter.UninitializedBuffer(requires_grad=False,
device=None, dtype=None, persistent=True)[source]#
```

Detailed Documentation

Documentation

A buffer that is not initialized.

Uninitialized Buffer is a a special case of `torch.Tensor` where the shape of the data is still unknown.

Unlike a `torch.Tensor`, uninitialized parameters hold no data and attempting to access some properties, like their shape, will throw a runtime error. The only operations that can be performed on a uninitialized parameter are changing its datatype, moving it to a different device and converting it to a regular `torch.Tensor`.

The default device or dtype to use when the buffer is materialized can be set during construction using e.g. `device='cuda'`.