

UninitializedParameter#

<https://pytorch.org/docs/stable/generated/torch.nn.parameter.UninitializedParameter.html>

Description:

A parameter that is not initialized. Uninitialized Parameters are a special case of `torch.nn.Parameter` where the shape of the data is still unknown. Unlike a `torch.nn.Parameter`, uninitialized parameters hold no data and attempting to access some properties, like their shape, will throw a runtime error. The only operations that can be performed on a uninitialized parameter are changing its datatype, moving it to a different device and converting it to a regular `torch.nn.Parameter`. The default device or dtype to use when the parameter is materialized can be set during construction using e.g. `device='cuda'`.

Function Signature

```
class
torch.nn.parameter.UninitializedParameter(requires_grad=True
, device=None, dtype=None)[source]#
cls_to_become[source]#
```

Detailed Documentation

Documentation

A parameter that is not initialized.

Uninitialized Parameters are a special case of `torch.nn.Parameter` where the shape of the data is still unknown.

Unlike a `torch.nn.Parameter`, uninitialized parameters hold no data and attempting to access some properties, like their shape, will throw a runtime error. The only operations that can be performed on a uninitialized parameter are changing its datatype, moving it to a different device and converting it to a regular `torch.nn.Parameter`.

The default device or dtype to use when the parameter is materialized can be set during construction using e.g. `device='cuda'`.