

torch.nn.utils.fuse_conv_bn_eval#

[https://pytorch.org/docs/stable/generated/torch.nn.utils.fuse_conv_bn_eval.h](https://pytorch.org/docs/stable/generated/torch.nn.utils.fuse_conv_bn_eval.html)

Description:

Fuse a convolutional module and a BatchNorm module into a single, new convolutional module. `conv` (`torch.nn.modules.conv._ConvNd`) – A convolutional module. `bn` (`torch.nn.modules.batchnorm._BatchNorm`) – A BatchNorm module. `transpose` (`bool`, optional) – If `True`, transpose the convolutional weight. Defaults to `False`. The fused convolutional module.

Function Signature

```
torch.nn.utils.fuse_conv_bn_eval(conv, bn, transpose=False)
[source]#
```

Parameters

Returns

Return type

Returns:

`torch.nn.modules.conv._ConvNd`

Notes & Warnings

NOTE

Note Both `conv` and `bn` must be in eval mode, and `bn` must have its running buffers computed.

Detailed Documentation

Documentation

Fuse a convolutional module and a BatchNorm module into a single, new convolutional module.

`conv` (`torch.nn.modules.conv._ConvNd`) – A convolutional module.

`bn` (`torch.nn.modules.batchnorm._BatchNorm`) – A BatchNorm module.

`transpose` (`bool`, optional) – If `True`, transpose the convolutional weight. Defaults to `False`.

The fused convolutional module.

`torch.nn.modules.conv._ConvNd`

Both conv and bn must be in eval mode, and bn must have its running buffers computed.

Fuse a convolutional module and a BatchNorm module into a single, new convolutional module.

conv (torch.nn.modules.conv._ConvNd) – A convolutional module.

conv (torch.nn.modules.conv._ConvNd) – A convolutional module.

bn (torch.nn.modules.batchnorm._BatchNorm) – A BatchNorm module.

bn (torch.nn.modules.batchnorm._BatchNorm) – A BatchNorm module.

transpose (bool, optional) – If True, transpose the convolutional weight. Defaults to False.

transpose (bool, optional) – If True, transpose the convolutional weight. Defaults to False.

The fused convolutional module.

torch.nn.modules.conv._ConvNd

Both conv and bn must be in eval mode, and bn must have its running buffers computed.