

torch.optim.Optimizer.register_load_state_dict_hook

https://pytorch.org/docs/stable/generated/torch.optim.Optimizer.register_load_state_dict_hook.html

Description:

Register a `load_state_dict` pre-hook which will be called before `load_state_dict()` is called. It should have the following signature: The `optimizer` argument is the optimizer instance being used and the `state_dict` argument is a shallow copy of the `state_dict` the user passed in to `load_state_dict`. The hook may modify the `state_dict` inplace or optionally return a new one. If a `state_dict` is returned, it will be used to be loaded into the optimizer. The hook will be called with argument `self` and `state_dict` before calling `load_state_dict` on `self`. The registered hook can be used to perform pre-processing before the `load_state_dict` call is made.

`hook` (Callable) – The user defined hook to be registered.

`prepend` (bool) – If True, the provided pre hook will be fired before all the already registered pre-hooks on `load_state_dict`. Otherwise, the provided hook will be fired after all the already registered pre-hooks. (default: False)

Function Signature

```
Optimizer.register_load_state_dict_pre_hook(hook,  
prepend=False)[source]#
```

Parameters

Returns

Return type

Returns:

torch.utils.hooks.RemoveableHandle

Code Examples

```
hook(optimizer, state_dict) -> state_dict or None
```

Detailed Documentation

Documentation

Register a `load_state_dict` pre-hook which will be called before `load_state_dict()` is called. It should have the following signature:

The `optimizer` argument is the optimizer instance being used and the `state_dict` argument is a shallow copy of the `state_dict` the user passed in to `load_state_dict`. The hook may modify the `state_dict` inplace or optionally return a new one. If a `state_dict` is returned, it will be used to be loaded into the optimizer.

The hook will be called with argument `self` and `state_dict` before calling `load_state_dict` on `self`. The registered hook can be used to perform pre-processing before the `load_state_dict` call is made.

`hook` (Callable) – The user defined hook to be registered.

`prepend` (bool) – If `True`, the provided pre hook will be fired before all the already registered pre-hooks on `load_state_dict`. Otherwise, the provided hook will be fired after all the already registered pre-hooks. (default: `False`)

a handle that can be used to remove the added hook by calling `handle.remove()`

`torch.utils.hooks.RemoveableHandle`