

torch.optim.Optimizer.register_state_dict_hook

https://pytorch.org/docs/stable/generated/torch.optim.Optimizer.register_state_dict_hook.html

Description:

Register a state dict post-hook which will be called after `state_dict()` is called. It should have the following signature: The hook will be called with arguments `self` and `state_dict` after generating a `state_dict` on `self`. The hook may modify the `state_dict` inplace or optionally return a new one. The registered hook can be used to perform post-processing on the `state_dict` before it is returned.

`hook` (Callable) – The user defined hook to be registered.

`prepend` (bool) – If True, the provided post hook will be fired before all the already registered post-hooks on `state_dict`. Otherwise, the provided hook will be fired after all the already registered post-hooks. (default: False)

Function Signature

```
Optimizer.register_state_dict_post_hook(hook, prepend=False)  
[source]#
```

Parameters

Returns

Return type

Returns:

`torch.utils.hooks.RemoveableHandle`

Code Examples

```
hook(optimizer, state_dict) -> state_dict or None
```

Detailed Documentation

Documentation

Register a state dict post-hook which will be called after `state_dict()` is called.

It should have the following signature:

The hook will be called with arguments `self` and `state_dict` after generating a `state_dict` on `self`. The hook may modify the `state_dict` inplace or optionally return a new one. The registered hook can be used to perform post-processing on the `state_dict` before it is returned.

`hook` (Callable) – The user defined hook to be registered.

`prepend` (bool) – If `True`, the provided post hook will be fired before all the already registered post-hooks on `state_dict`. Otherwise, the provided hook will be fired after all the already registered post-hooks. (default: `False`)

a handle that can be used to remove the added hook by calling `handle.remove()`

`torch.utils.hooks.RemoveableHandle`