

ConstantLR#

https://pytorch.org/docs/stable/generated/torch.optim.lr_scheduler.ConstantLR.html

Description:

Multiply the learning rate of each parameter group by a small constant factor. The multiplication is done until the number of epoch reaches a pre-defined milestone: `total_iters`. Notice that such multiplication of the small constant factor can happen simultaneously with other changes to the learning rate from outside this scheduler. When `last_epoch=-1`, sets initial lr as `lr.optimizer` (Optimizer) – Wrapped optimizer. `factor` (float) – The number we multiply learning rate until the milestone. Default: 1./3. `total_iters` (int) – The number of steps that the scheduler multiplies the learning rate by the factor. Default: 5.

Function Signature

```
class torch.optim.lr_scheduler.ConstantLR(optimizer,  
factor=0.3333333333333333, total_iters=5, last_epoch=-1)  
[source]#
```

Parameters

```
get_last_lr()[source]#
```

Return type

```
get_lr()[source]#
```

Returns:

```
dict[str, Any]
```

Code Examples

```
>>> # Assuming optimizer uses lr = 0.05 for all groups
>>> # lr = 0.025   if epoch == 0
>>> # lr = 0.025   if epoch == 1
>>> # lr = 0.025   if epoch == 2
>>> # lr = 0.025   if epoch == 3
>>> # ...
>>> # lr = 0.05     if epoch >= 40
>>> scheduler = ConstantLR(optimizer, factor=0.5,
total_iters=40)
>>> for epoch in range(100):
>>>     train(...)
>>>     validate(...)
>>>     scheduler.step()
```

Detailed Documentation

Documentation

Multiply the learning rate of each parameter group by a small constant factor.

The multiplication is done until the number of epoch reaches a pre-defined milestone: `total_iters`. Notice that such multiplication of the small constant factor can happen simultaneously with other changes to the learning rate from outside this scheduler. When `last_epoch=-1`, sets initial lr as lr.

`optimizer (Optimizer)` – Wrapped optimizer.

`factor` (float) – The number we multiply learning rate until the milestone. Default: 1./3.

`total_iters` (int) – The number of steps that the scheduler multiplies the learning rate by the factor. Default: 5.

`last_epoch` (int) – The index of the last epoch. Default: -1.

Return last computed learning rate by current scheduler.

Compute the learning rate of each parameter group.

Load the scheduler's state.

`state_dict` (dict) – scheduler state. Should be an object returned from a call to `state_dict()`.

Return the state of the scheduler as a dict.

It contains an entry for every variable in `self.__dict__` which is not the optimizer.