

LambdaLR#

[https://pytorch.org/docs/stable/generated/torch.optim.lr_scheduler.LambdaLR.](https://pytorch.org/docs/stable/generated/torch.optim.lr_scheduler.LambdaLR.html)

Description:

Sets the initial learning rate. The learning rate of each parameter group is set to the initial lr times a given function. When `last_epoch=-1`, sets initial lr as lr. optimizer (Optimizer) – Wrapped optimizer. lr_lambda (function or list) – A function which computes a multiplicative factor given an integer parameter epoch, or a list of such functions, one for each group in optimizer.param_groups. last_epoch (int) – The index of last epoch. Default: -1.

Function Signature

```
class torch.optim.lr_scheduler.LambdaLR(optimizer,  
lr_lambda, last_epoch=-1)[source]#
```

Parameters

```
get_last_lr()[source]#
```

Return type

```
get_lr()[source]#
```

Returns:

dict[str, Any]

Code Examples

```
>>> # Assuming optimizer has two groups.
>>> num_epochs = 100
>>> lambda1 = lambda epoch: epoch // 30
>>> lambda2 = lambda epoch: 0.95**epoch
>>> scheduler = LambdaLR(optimizer, lr_lambda=[lambda1,
lambda2])
>>> for epoch in range(num_epochs):
>>>     train(...)
>>>     validate(...)
>>>     scheduler.step()
>>>
>>> # Alternatively, you can use a single lambda function for
all groups.
>>> scheduler = LambdaLR(opt, lr_lambda=lambda epoch: epoch //
30)
>>> for epoch in range(num_epochs):
>>>     train(...)
>>>     validate(...)
>>>     scheduler.step()
```

Detailed Documentation

Documentation

Sets the initial learning rate.

The learning rate of each parameter group is set to the initial lr times a given function. When `last_epoch=-1`, sets initial lr as lr.

`optimizer (Optimizer)` – Wrapped optimizer.

`lr_lambda (function or list)` – A function which computes a multiplicative factor given an integer parameter `epoch`, or a list of such functions, one for each group in `optimizer.param_groups`.

`last_epoch (int)` – The index of last epoch. Default: -1.

Return last computed learning rate by current scheduler.

Compute learning rate.

Load the scheduler's state.

When saving or loading the scheduler, please make sure to also save or load the state of the optimizer.

`state_dict (dict)` – scheduler state. Should be an object returned from a call to `state_dict()`.

Return the state of the scheduler as a dict.

It contains an entry for every variable in `self.__dict__` which is not the optimizer. The learning rate lambda functions will only be saved if they are callable objects and not if they are functions or lambdas.

When saving or loading the scheduler, please make sure to also save or load the state of the optimizer.

